

# Quadrat 230V



230V, 50-60Hz, Class II, IP23\*, GU10, Max 35W

	h (min.)	
Quadrat 35W	150mm	1xØ120mm
Quadrat 2x35W	150mm	2xØ120mm
Quadrat 3x35W	200mm	3xØ120mm
Quadrat 7W LED	150mm	1xØ120mm
Quadrat 2x7W LED	150mm	2xØ120mm
Quadrat 3x7W LED	200mm	3xØ120mm

35W Halogen:

7W LED:

NO: Minimumsavstand til brennbar materiale i armaturens stråleretning.  
 EN: Minimum distance to flammable material in the beam direction.  
 FR: Distance minimum entre le faisceau lumineux de l'armature et toute matière inflammable.  
 NL: Minimale afstand tussen de lichtstraal van de armatuur en het brandbaar materiaal.  
 DE: Der kleinste Abstand zum brennbaren Material in die Richtung des Lichtstrahls.

Halopar 16,  
240V, 35W, 35°

ca 10° (max. 20°)  
Max 16A

Philips Master LED MV  
Reflector, 7W, GU10,  
230-240V, 25°, 1000cd,  
50-60Hz, typ. 45mA

SG Downlightbox

SG Sealbox & Frame

Rev. 16.05.2011

SG Armaturen AS  
Svaabekk Industriområde  
N-4790 Lillesand  
NORGE  
Tel: +47 37 26 84 84  
www.sg-as.no

SG Armaturen AB  
August Barksg. 30B  
SE-421 32 Västra Frölunda  
SVERIGE  
Tel: +46 31 81 71 10  
www.sg-ab.se

SG Lighting SA/NV  
Wayenborgstraat 4  
B-2800 Mechelen Noord II  
BELGIQUE/BELGIË  
Tel: +32 (0) 15 20 72 71  
www.sglighting.net

SG Lighting SA/NV  
Parc de l'Arboretum  
73 rue de Saint Mandrier  
83140 Six Fours Les Plages  
FRANCE  
Tel: +33 04 94 93 00 00  
www.sglighting.net

SG Leuchten GmbH  
Nordstrasse 53  
D-59399 Olfen  
DEUTSCHLAND  
Tel: 0152-57000500  
www.sg-leuchten.de

# Quadrat 12V



12V, max 35W, GX5.3, Class III, IP23\*

	<table border="1"> <thead> <tr> <th></th> <th>h (min.)</th> <th></th> </tr> </thead> <tbody> <tr> <td>Quadrat 35W</td> <td>150mm</td> <td>1xØ120mm</td> </tr> <tr> <td>Quadrat 2x35W</td> <td>150mm</td> <td>2xØ120mm</td> </tr> <tr> <td>Quadrat 3x35W</td> <td>200mm</td> <td>3xØ120mm</td> </tr> </tbody> </table>		h (min.)		Quadrat 35W	150mm	1xØ120mm	Quadrat 2x35W	150mm	2xØ120mm	Quadrat 3x35W	200mm	3xØ120mm	
	h (min.)													
Quadrat 35W	150mm	1xØ120mm												
Quadrat 2x35W	150mm	2xØ120mm												
Quadrat 3x35W	200mm	3xØ120mm												
		<p>NO: Minimumsavstand til brennbart materiale i armaturens stråleretning.          EN: Minimum distance to flammable material in the beam direction.          FR: Distance minimum entre le faisceau lumineux de l'armature et toute matière inflammable.          NL: Minimale afstand tussen de lichtstraal van de armatuur en het brandbaar materiaal.          DE: Der kleinste Abstand zum brennbaren Material in die Richtung des Lichtstrahls.</p>												
		<p>NO: Skadet glass må erstattes med nytt.          EN: Damaged glass must be replaced.          FR: Tout verre endommagé doit être remplacé.          NL: Gebroken glas moet vervangen worden.          DE: Glasscherben müssen ausgetauscht werden.</p>												
<p>* </p>														
<p>SG Downlightbox </p>		<p>SG Sealbox &amp; Frame </p>												

Rev. 26.05.2011

SG Armaturen AS  
 Svaabekk Industriområde  
 N-4790 Lillesand  
 NORGE  
 Tel: +47 37 26 84 84  
 www.sg-as.no

SG Armaturen AB  
 August Barksg. 30B  
 SE-421 32 Västra Frölunda  
 SVERIGE  
 Tel: +46 31 81 71 10  
 www.sg-ab.se

SG Lighting SA/NV  
 Wayenborgstraat 4  
 B-2800 Mechelen Noord II  
 BELGIQUE/BELGIË  
 Tel: +32 (0) 15 20 72 71  
 www.sglighting.net

SG Lighting SA/NV  
 Parc de l'Arboretum  
 73 rue de Saint Mandrier  
 83140 Six Fours Les Plages  
 FRANCE  
 Tel: +33 04 94 93 00 00  
 www.sglighting.net

SG Leuchten GmbH  
 Nordstrasse 53  
 D-59399 Olfen  
 DEUTSCHLAND  
 Tel: 0152-57000500  
 www.sg-leuchten.de